



Dano OP15D-301

| Typical Specification | | 15.6 inch LCD Open Frame (16 : 9) |
|--|-------------------|--|
| Model No. | | 15.6" w (VGA + DVI) |
| LCD Panel Type | | 15.6" Diagonal WXGA |
| Maximum Resolution | | 1366 (H) x 768 (V) |
| Active Display Area | | 344.23 (H) x 193.53 (V) mm |
| Pixel Dimension | | 0.252(H) x 0.252(V) mm |
| Brightness | | 220 cd/m ² (Typical) |
| Contrast Ratio | | 500:1 (Typical) |
| Response Time (Tr/Tf) | | 11 ms |
| Backlight Unit | | LED |
| Viewing Angle | | Horizontal -45°/+45°(90°); Vertical-25°/+45°(65°) |
| Graphic Input(Rear) | | Input . RGB D-Sub 15 pin x1, DVI x1 |
| AC /DC Adapter | | AC 90~264 V / 50~60Hz |
| Power | Power consumption | < 24W |
| | Stand-by | < 5W |
| OSP™ (On-Screen Programmer) Screen Controls | | Auto Adjust, Brightness, Contrast, Colour Temperature (9300, 7500, 6500°K, RGB, sRGB, Auto Colour), R/G/B-Gain, H/V-position, Phase, Clock, Language Selection, Input Signal Selection, OSP Setup, Volume Adjust, Recall |
| Language Supported | | English, French, German, Spanish, Italian, Japanese, Chinese |

| | |
|-----------------------|--|
| Resolutions Supported | VGA 640x350 @ 70Hz, 640x400 @ 56/70Hz, 640x480@60/67/72/75Hz, 720x400 @70Hz, SVGA 800x600 @56/60/72/75Hz, XGA 1024x768 @60/70/72/75Hz, WXGA HD 1366 x768@60Hz |
| Touch Panel | DanoTech W1-15782APA-N0 |



